



## Screwless Connectors Block Connectors

# 930-02/ 2



### Order Info

|                             |               |
|-----------------------------|---------------|
| reference number (ref. no.) | 112402        |
| PU                          | 1,000         |
| EAN                         | 4028012104260 |

### Type

|                 |                                    |
|-----------------|------------------------------------|
| Type            | terminal block with 2 release keys |
| connection type | push-in                            |
| number of poles | 2 pole                             |
| colour          | white                              |

### Electrical Data

|               |       |
|---------------|-------|
| rated voltage | 450 V |
| rated current | 24 A  |

### Connection Data

|                            |                           |
|----------------------------|---------------------------|
| cross-section rating       | 2.5 mm <sup>2</sup>       |
| cross-section rating (UL)  | 20-14 AWG                 |
| clamping range internal    | 0.5 - 2.5 mm <sup>2</sup> |
| clamping range external    | 0.5 - 2.5 mm <sup>2</sup> |
| type of conductor internal | solid                     |
| type of conductor external | solid                     |
| stripping length           | 8.0 - 9.0 mm              |
| clamping units per pole    | 2                         |

### Ambient Conditions

|   |       |
|---|-------|
| T <sub>max</sub> ambient air (at rated current) | 85 °C |
|---|-------|

### Materials

|                                   |       |
|-----------------------------------|-------|
| insulator material                | PA    |
| contact material                  | brass |
| flammability rating acc. to UL 94 | V-2   |

### Approvals

|                  |     |
|------------------|-----|
| acc. to EN 60998 | yes |
|------------------|-----|

acc. to UL yes

---

acc. to CSA yes

---