



## Screw Terminal Blocks

# 230/ 3

### Order Info

reference number (ref. no.)	121203
PU	2,000
EAN	4028012105175



### Type

Type	Terminal Block
connection type	screw
number of poles	3 pole
colour	naturalal

### Electrical Data

rated voltage	450 V
rated current	24 A

### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 7.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	5.0 - 5.5 mm
fixing	Screw
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\cup$ 0.5 Nm
mounting hole diameter	2.8 mm
socket diameter	3.10 mm
pin spacing	8.0 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C

### Materials

insulator material	PA
contact material	brass
flammability rating acc. to UL 94	V-2

## Approvals

<b>acc. to EN 60998</b>	yes
<b>acc. to UL</b>	yes
<b>acc. to CSA</b>	yes

## Accessories

<b>230 BZ/ 3</b>	191203
<b>ZEL 110</b>	196420