



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 180 basic
AC 180 SK/ 3 SL



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 19066 |
| PU | 200 |
| EAN | 4028012167166 |

Type

| | |
|-----------------|----------------|
| Type | Terminal Block |
| connection type | screw |
| number of poles | 3 pole |
| colour | black |

Electrical Data

| | |
|---------------|--------|
| rated voltage | 450 V |
| rated current | 17.5 A |

Connection Data

| | |
|-------------------------|--------------------------------|
| cross-section rating | 4.0 mm ² |
| type of conductor | fine stranded, stranded, solid |
| stripping length | 8.0 mm |
| dismantling length | 30.0 mm |
| clamping units per pole | 1 |
| contact screw assembly | 0.5 x 3.0 / \cup 0.5 Nm |

Ambient Conditions

| | |
|---|--------|
| T _{max} ambient air (at rated current) | 85 °C |
| T _{max} component (operation) | 125 °C |
| T _{min} component (operation) | -40 °C |
| IP Code acc. to EN 60529 | IP68 |

Materials

| | |
|-----------------------------------|-------|
| insulator material | PA |
| contact material | brass |
| flammability rating acc. to UL 94 | V-2 |