



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 180 basic

AC 180 SKG-T D24



Order Info

reference number (ref. no.)	19079
PU	200
EAN	4028012122936

Type

Type	T-housing
colour	black

Connection Data

sheathing cable diameter	7.0 - 13.5 mm
--------------------------	---------------

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C
IP Code acc. to EN 60529	IP68

Materials

insulator material	PA
flammability rating acc. to UL 94	V-2

Approvals

Accessories

AC 180 SK/ 2 SL	19057
AC 180 SK/ 3 SL	19066
AC 180 SK/ 3+3 SL	19058
AC 180 SK/ 4 SL	19069
AC 180 SK/ 5 SL	19074
AC 180 SK/ 6 SL	19076
AC 169 WKZ SW21/24	749960
DR 16 RH	729011
DR 16 GS	729032
DR 16 1x14,0	729031

DR 16 1x4,0	729033
DR 16 1x6,5	729034
DR 16 2x4,0	729035
DR 16 2x5,5	729036
DR 16 3x4,0	729037
DR 16 4x3,5	729038
DR 16 5x3,5	729009