




## Fused Terminal Blocks

### 503 SI/ 3 E DS GW

#### Order Info

reference number (ref. no.)	19948
PU	200
EAN	4028012143924



#### Type

Type	screw terminal block with PE contact to the base plate
connection type	screw
number of poles	3 pole
colour	naturalal
wire protection	yes

#### Electrical Data

rated voltage	400 V
rated current	10 A

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 5.5 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
type of conductor internal	fine stranded, stranded, solid
type of conductor external	fine stranded, stranded, solid
stripping length	7.0 - 7.5 mm
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\cup$ 0.5 Nm
mounting hole diameter	3.1 mm
socket diameter	2.75 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C

#### Materials

insulator material	PA GW
contact material	brass

**flammability rating acc. to UL 94**

V-2

---

## Approvals

## Accessories

---

**ZEL 110**

196420

---

**ABK 503/ 3 GW**

193813

---