



Screwless Connectors  
Luminaire Connectors

LK 980-01/ 3 SK BD N PE L



Order Info

reference number (ref. no.)	21756
PU	500
EAN	4028012112890

Type

Type	Terminal Block
connection type	push-in
number of poles	3 pole
colour	white
PE-terminal	SK

Electrical Data

rated voltage	450 V
rated current	24 A

Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	20-14 AWG
clamping range internal	0.5 - 2.5 mm <sup>2</sup>
clamping range external	0.5 - 1.5 mm <sup>2</sup>
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length	8.0 - 9.0 mm
fixing	Screw
clamping units per pole	2
pole marking	N ⊕ L

Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
ammonia resistance	yes

Materials

insulator material	PA
contact material	spring steel, copper

<b>flammability rating acc. to UL 94</b>	V-2
--	-----

---

## Approvals

---

<b>acc. to EN 60998</b>	yes
-------------------------	-----

---

<b>acc. to UL</b>	yes
-------------------	-----

---

## Accessories

---

<b>WKZ 980-01</b>	999041
-------------------	--------

---

<b>ZEL 110</b>	196420
----------------	--------

---

<b>ZEL 900</b>	196423
----------------	--------

---