



Circular Connectors IP68
Circular Connectors AC 173 click
AC 173 REBUP/5 M20



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 26021 |
| PU | 200 |
| EAN | 4028012174294 |

Type

| | |
|---------------------------------------|--------------------|
| Type | panel mount socket |
| connection type | push-in |
| number of poles | 5 pole |
| colour | black |
| protection against incorrect plugging | yes |

Electrical Data

| | |
|-----------------------|--------|
| rated voltage | 500 V |
| rated current | 17.5 A |
| rated impulse voltage | 2.5 kV |

Connection Data

| | |
|-------------------------|----------------------------|
| clamping range | 0.25 - 1.5 mm ² |
| stripping length | 12.0 mm |
| dismantling length | 25.0 mm |
| clamping units per pole | 1 |
| lock nut assembly | 1.5 Nm |
| housing hole | M20 |
| pole marking | 1-2-3/L-N-E |
| wall thickness | - 3.0 mm |

Ambient Conditions

| | |
|---|----------------|
| T _{max} ambient air (at rated current) | 60 °C |
| T _{max} component (operation) | 125 °C |
| T _{min} component (operation) | -40 °C |
| IP Code acc. to EN 60529 | IP66/IP68/IP69 |

Materials

| | |
|--------------------|--------|
| insulator material | PA 6.6 |
|--------------------|--------|

| | |
|--|-----|
| flammability rating acc. to UL 94 | V-0 |
|--|-----|

Approvals

| | |
|-------------------------|-----|
| acc. to EN 61984 | yes |
|-------------------------|-----|

Accessories

| | |
|---------------------|-------|
| AC 173 RWZ/5 | 26060 |
|---------------------|-------|

| | |
|--------------------|-------|
| AC 173 RVKB | 26032 |
|--------------------|-------|
