



Circular Terminal Blocks IP68
Circular Terminal Blocks AC 179 kompakt
AC 179 SKE/ 4 SL L M25



Order Info

reference number (ref. no.)	26757
PU	200

Type

Type	panel mount terminal block
connection type	screw
number of poles	4 pole
colour	black
centre stop	yes
strain relief	yes

Electrical Data

rated voltage	450 V
rated current	32 A

Connection Data

clamping range	0.5 - 4.0 mm ²
sheathing cable diameter	7.0 - 13.5 mm
type of conductor	fine stranded, stranded, solid
stripping length	6.0 mm
dismantling length	25.0 mm
clamping units per pole	1
lock nut assembly	1.5 Nm
grommet assembly	2.0 Nm
contact screw assembly	M3 - max. ⤵ 0.8 Nm
housing hole	M25
pole marking	1-2-3-4
wall thickness	1.0 - 7.0 mm
strain relief assembly	⤵ 2.5 Nm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{max} component (operation)	125 °C
T _{min} component (operation)	-40 °C

IP Code acc. to EN 60529	IP68/IP69
---------------------------------	-----------

Materials

insulator material	PA
contact material	brass
flammability rating acc. to UL 94	V-0

Approvals

acc. to EN 60998	yes
-------------------------	-----

Accessories

AC 179 RVK/ 4 M20	749564
AC 173 BC SW	26280
DR 16 1x14,0	729031
DR 16 1x4,0	729033
DR 16 1x6,5	729034
DR 16 2x4,0	729035
DR 16 2x5,5	729036
DR 16 3x4,0	729037
DR 16 4x3,5	729038
DR 16 5x3,5	729009
DR 16 RH	729011
DR 16 GS	729032